




EE811



IP41



## Presence detector 360°, 2 channels, flush mounted, white

### Technical characteristics

#### Main electrical features

Rated operational voltage Ue	230 V
Frequency	50 Hz

#### Dimensions

Width of installed product	100 mm
Recommended installation height	2.5...3.5 m

#### Measurement

Detection Method	Passive Infrared
------------------	------------------

#### Power supply

Supply voltage	230 V
----------------	-------

#### Detection

Detection angle	360 °
Detection angle	360 °
Detection field Ø, on floor	≈ 12 m
Detection field Ø, at desk height	≈ 5 m
Frontal detecting distance	7 m
Side detecting distance	13 m

#### Materials

Colour	pure white
RAL colour	RAL 9010 - Pure white
Material	plastic
Type of surface treatment	Untreated

#### Lighting control

Response brightness, adjustable	≈ 5...1200 lx
Brightness measurement range	5 / 1200 Lux

#### Installation, mounting

Maximum Mounting Height	4 m
-------------------------	-----

#### Settings

Response value sensitivity adjustable	Yes
Delay time, adjustable	≈ 1...30 mn

#### Equipment

Angle of horizontal detection	360 °
-------------------------------	-------

**Safety**

---

Protection index IP	IP41
Protection class	isol.class II

---

**Use conditions**

---

Operating temperature	0...45 °C
Storage/transport temperature	-10...60 °C

---

**Identification**

---

Application, usage	Motion detector
Main design line	Motion detectors

---