



MBN363



**MCB 3P 6kA B-63A 3M**

**Technical properties**

**Architecture**

Number of protected poles	3
Number of poles	3 P
Curve	B

**Functions**

Concurrently switching N-neutral	No
----------------------------------	----

**Configuration**

Number of modules	3
-------------------	---

**Connectivity**

Top connection alignment for modular devices	Aligned terminal
Bottom connection alignment for modular devices	Aligned terminal

**Main electrical features**

Rated short circuit breaking capacity $I_{cn}$ AC according IEC60898-1	6 kA
Rated operational voltage $U_e$	230 / 400 V
Type of supply voltage	AC
Frequency	50/60 Hz

**Voltage**

Rated insulation voltage	500 V
Rated impulse withstand voltage	4000 V

**Electric current**

Rated current	63 A
Rated service breaking capacity $I_{cs}$ AC according IEC 60898-1	6 kA
min/maxi threshold value of the AC thermal operation	1.13 / 1.45 $I_n$
Magnetic regulating current	3 / 5 $I_n$
min/maxi threshold value of the DC magnetic operation	4 / 7 $I_n$
min/maxi threshold value of the DC thermal operation	1.13 / 1.45 $I_n$
Breaking capacity on 1 pole for IT 400V NF 60947-2	3 kA
Rated short circuit breaking capacity $I_{cn}$ under 400V AC according IEC60898-1	6 kA

Rated ultimate short-circuit breaking capacity Icu under 400V AC IEC 60947-2	10 kA
--	-------

Rated ultimate short-circuit breaking capacity Icu under 415V AC IEC 60947-2	10 kA
--	-------

### Electric current / temperature

Rating current -25°C	78.4 A
----------------------	--------

Rating current -20°C	77 A
----------------------	------

Rating current -15°C	75.6 A
----------------------	--------

Rating current -10°C	74.1 A
----------------------	--------

Rating current -5°C	72.7 A
---------------------	--------

Rating current 0°C	71.3 A
--------------------	--------

Rating current 5°C	69.9 A
--------------------	--------

Rating current 10°C	68.5 A
---------------------	--------

Rating current 15°C	67.1 A
---------------------	--------

Rating current 20°C	65.6 A
---------------------	--------

Rating current 25°C	64.2 A
---------------------	--------

Rating current 30°C	63 A
---------------------	------

Rating current 35°C	61.4 A
---------------------	--------

Rating current 40°C	60 A
---------------------	------

Rating current 45°C	58.6 A
---------------------	--------

Rating current 50°C	57 A
---------------------	------

Rating current 55°C	55.7 A
---------------------	--------

Rating current 60°C	54.3 A
---------------------	--------

Rating current 65°C	52.9 A
---------------------	--------

Rating current 70°C	51.5 A
---------------------	--------

### Current correction factors

Correction factor of rating current for 2 devices placed side-by-side	1
---	---

Correction factor of rating current for 3 devices placed side-by-side	0.95
---	------

Correction factor of rating current for 4 and 5 devices placed side-by-side	0.9
---	-----

Correction factor of rating current for 6 devices placed side-by-side	0.85
---	------

Correction factor of magnetic tripping with 100 Hz	1.1
--	-----

Correction factor of magnetic tripping with 200 Hz	1.2
--	-----

Correction factor of magnetic tripping with 400 Hz	1.5
--	-----

Correction factor of magnetic tripping with 60 Hz	1
---	---

### Dimensions

Depth of installed product	70 mm
----------------------------	-------

Height of installed product	83 mm
-----------------------------	-------

Width of installed product	52.5 mm
----------------------------	---------

### Frequency

Frequency	50 to 60 Hz
-----------	-------------

**Power**

Total power loss under IN	18.3 W
Power loss per pole at In	6.4 W

**Endurance**

Electric endurance in number of cycles	4000
Number of mechanical operations	20000

**Installation, mounting**

Type of top connection for modular devices	with screw
Tightening torque	2,8Nm
Type of Bottom Connection for modular devices	Blconnect

**Connection**

Connection cross-section of input and output with screws, for massive conductors	1 / 35 mm <sup>2</sup>
Connection cross section of access and exit with screws, for flexible conductor	1 / 25 mm <sup>2</sup>
Type of connection	with screw

**Standards**

Standard text	EN 60898-1
---------------	------------

**Safety**

Protection index IP	IP20
RoHS conform	Yes
Halogen free	No

**Use conditions**

Operating temperature	-25...70 °C
Degree of pollution according to IEC 60664 / IEC 60947-2	2
Class of energy limitation I <sup>2</sup> t	3
Altitude	2000 m
Air humidity protection	for all climates
Storage/transport temperature	-25...80 °C