



LF316G

Cylindrical fuse-links for industrial applications 10x38mm gG 16A 500V AC 120kA

Technical properties

Functions

| | |
|------------------------------|----------|
| Release characteristic fuses | Time-lag |
|------------------------------|----------|

Main electrical features

| | |
|--|--------|
| Rated short circuit breaking capacity I_{cn} AC according IEC60898-1 | 120 kA |
|--|--------|

| | |
|---------------------------------|-------|
| Rated operational voltage U_e | 500 V |
|---------------------------------|-------|

| | |
|------------------------|----|
| Type of supply voltage | AC |
|------------------------|----|

Electric current

| | |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

| | |
|--|--------|
| Rated ultimate short-circuit breaking capacity I_{cu} AC IEC 60947-2 | 120 kA |
|--|--------|

Fuse

| | |
|-------------|----|
| CharactFuse | gG |
|-------------|----|

Frequency

| | |
|-----------|-------------|
| Frequency | 50 to 60 Hz |
|-----------|-------------|

Power

| | |
|------------------------------|-------|
| Total power loss under I_N | 1.6 W |
|------------------------------|-------|

Standards

| | |
|-------------------------|-----------|
| European directive WEEE | concerned |
|-------------------------|-----------|

Safety

| | |
|---------------|-----|
| REACH conform | Yes |
|---------------|-----|

| | |
|--------------|-----|
| RoHS conform | Yes |
|--------------|-----|

| | |
|--------------|-----|
| Halogen free | Yes |
|--------------|-----|