



ESC080

**Auxiliary contact 6A, 1NO+1NC**

**Technical properties**

**Configuration**

Number of modules	0.5
-------------------	-----

**Main electrical features**

Rated operational voltage Ue	230 V
------------------------------	-------

**Voltage**

Rated insulation voltage	240 V
--------------------------	-------

Rated impulse withstand voltage	4 kV
---------------------------------	------

**Electric current**

Acceptable current rating with AC1	6 A
------------------------------------	-----

Rated current	6 A
---------------	-----

**Dimensions**

Depth of installed product	60 mm
----------------------------	-------

Height of installed product	83 mm
-----------------------------	-------

Width of installed product	11 mm
----------------------------	-------

**Power**

Total power loss under IN	0.1 W
---------------------------	-------

**Endurance**

Electric endurance in number of cycles	30000
--	-------

Number of mechanical operations	1000000
---------------------------------	---------

**Connection**

Number of contacts	2
--------------------	---

Type of connection	with screw
--------------------	------------

Connection cross-section of the control cable solid	1 / 10 mm <sup>2</sup>
---	------------------------

**Safety**

Protection class	isol.class II
------------------	---------------

REACH conform	Yes
---------------	-----

RoHS conform	Yes
--------------	-----

Halogen free	Yes
--------------	-----

**Use conditions**

Operating temperature	-10...50 °C
-----------------------	-------------

Storage/transport temperature	-40...80 °C
-------------------------------	-------------