



ERC218

**Relay 16A, 1NO+1NC, 230V~50Hz**

**Technical properties**

**Configuration**

Number of modules	1
-------------------	---

**Main electrical features**

Rated operational voltage Ue	230 V
Frequency	50 Hz

**Voltage**

Rated insulation voltage	250 V
DC control voltage	0 V
Command voltage AC	230 V
Rated impulse withstand voltage	4 kV

**Electric current**

Rated current	16 A
Thermal rated current outside of housings	16 A
Acceptable current load with AC7 category A	16 A
Acceptable current load with AC7 category B	5.5 A

**Dimensions**

Depth of installed product	60 mm
Height of installed product	83 mm
Width of installed product	17.85 mm

**Power**

Inrush power absorbed	10.7 VA
Operating consumption	2.9 VA
Total power loss under IN	2 W
Power loss per contact	1 W
Power dissipation per coil	1 W
Contact rating with 230 V in AC7 category A	3 kW
Contact rating with 230 V in AC7 category B	880 W

**Tripping**

Time of response when opening	15 ms
Time of response when closing	25 ms

**Endurance**

Electric endurance in number of cycles	30000
--	-------

Number of mechanical operations 100000

---

**Fluorescent bulbs control**

Max. power with fluorescent parallel lamps 490 VA

Fluorescent lamps in duo circuit 1200 VA

Max. load fluorescent lamp 570 VA

---

**Incandescent bulbs control**

Max. power with incandescent lamps 1100 W

---

**Installation, mounting**

Tightening torque 1,2Nm

---

**Connection**

Connection cross-section of the control cable solid 1 / 10 mm<sup>2</sup>

---

**Equipment**

Quantity of NC contacts 1

Quantity of NO contacts 1

Can be accessorized Yes

---

**Use**

Local operation/hand operation Yes

---

**Safety**

REACH conform Yes

RoHS conform Yes

Halogen free No

---

**Use conditions**

Operating temperature -10...50 °C

Storage/transport temperature -40...80 °C