Product data sheet ESC463S





ESC463S

Humfree Contactor 63A, 4NO, 230V~50/60Hz

Technical properties

Number of poles	4 P
Configuration	
Number of modules	3
Main electrical features	
Rated operational voltage Ue	400 V
Frequency	50 Hz
Voltage	
Rated insulation voltage	440 V
DC control voltage	0 V
Command voltage AC	230 V
Rated impulse withstand voltage	4 kV
Electric current	
Rated current	63 A
Thermal rated current outside of housings	63 A
Acceptable current load with AC7 category A	63 A
Acceptable current load with AC7 category B	32 A
Dimensions	
Depth of installed product	60 mm
Height of installed product	85 mm
Width of installed product	54 mm
Power	
Inrush power absorbed	5.2 VA
Operating consumption	5.2 VA
Total power loss under IN	24.5 W
Power loss per contact	5 W
Power dissipation per coil	4.5 W
Contact rating with 230 V in AC7 category A	11.6 kW
Contact rating with 230 V in AC7 category B	3.3 kW
Contact rating with 400 V in AC7 category A	35 kW
Contact rating with 400 V in AC7 category B	10 kW

Tripping

Time of response when opening	20 ms
Time of response when closing	25 ms
Resistance	
Winding resistance	9200 Ω
Endurance	
Electric endurance in number of cycles	30000
Number of mechanical operations	1000000
Fluorescent bulbs control	
Max. power with fluorescent parallel lamps	2100 VA
Fluorescent lamps in duo circuit	4700 VA
Max. load fluorescent lamp	3000 VA
Incandescent bulbs control	
Max. power with incandescent lamps	6500 W
Installation, mounting	
Tightening torque	Coil: 2,5Nm ; Power: 3,5Nm
Connection	
Number of contacts	4
Type of connection	with screw
Connection cross-section of the control	
cable solid	1 / 2.5 mm²
Equipment	1 / 2.5 mm²
Equipment	
Equipment Can be accessorized	Yes
Equipment Can be accessorized Use	Yes
Equipment Can be accessorized Use Local operation/hand operation	Yes
Equipment Can be accessorized Use Local operation/hand operation Safety	Yes No isol.class II
Equipment Can be accessorized Use Local operation/hand operation Safety Protection class	Yes No isol.class II No
Equipment Can be accessorized Use Local operation/hand operation Safety Protection class REACH conform	Yes No isol.class II No Yes
Equipment Can be accessorized Use Local operation/hand operation Safety Protection class REACH conform RoHS conform	1 / 2.5 mm² Yes No isol.class II No Yes No
Equipment Can be accessorized Use Local operation/hand operation Safety Protection class REACH conform RoHS conform Halogen free	Yes No isol.class II No Yes