



LF2002009010A

Trunking with adhesive tape from PVC LF 20x20mm pure white

Technical properties

Architecture

Fixing mode bottom punched

Configuration

Antibacterial treatment No

Connectivity

Trunking coupling without coupler

Dimensions

Trunking height 18 mm

Length 2000 mm

Trunking width 19 mm

Capacity

Maximum number of cables (Ø 11 mm, 50% fill) 1

Maximum number of cables (Ø 11 mm, 50% fill) 1

Cover, door

Lid shape premounted

Materials

Colour pure white

RAL colour RAL 9010 - Pure white

Material PVC

Material group plastic

Type of surface treatment untreated

Transparent No

Cable

Internal/useful cross section 228 mm²

Equipment

Number of fix dividers 0

Number of plugable separators 0

Compartment quantity 1

Cable retainers per meter 0

Standards

European directive RoHS voluntary compliance

Safety

| | |
|---------------------|------|
| Protection index IP | IP30 |
| REACH conform | Yes |
| RoHS conform | Yes |
| Halogen free | No |
| Impact strength | IK07 |

Use conditions

| | |
|-----------------------|------------|
| Operating temperature | -5...60 °C |
|-----------------------|------------|

temperatur

| | |
|---------------------|------------|
| Ambient temperature | -5...65 °C |
|---------------------|------------|
