



FL125A

**Steel enclosure, Orion.Plus, plain door 950x600x250 mm**

**Technical properties**

**Architecture**

Fixing mode Wall mounting

**Functions**

Cover with overpressure release No

**Configuration**

Number of modules 156

**Compatibility**

Suitable for lightning protection No

**Electric current**

Rated current 630 A

**Dimensions**

Insertion depth 250 mm

Depth of installed product 250 mm

Internal depth 250 mm

Height of installed product 950 mm

Width of installed product 600 mm

Thickness of sidewall material 2 mm

**Cover, door**

Material thickness cover 2 mm

Type of door closing lock with male triangular wrench

Interlockable Yes

Number of keylock of the door 2

Cover type Closed (plain)

Door leave single

Transparent cover or door No

**Materials**

Colour RAL 7035

Colour light grey

RAL colour RAL 7035 - Light grey

Material Steel

Type of surface treatment powder-coated

**Installation, mounting**

Suitable for outdoor use No

Subject to technical modifications

**Equipment**

---

Number of rows	6
Number of keys	2
Number of openings for flange plates	2
Extension possible	Yes

**Standards**

---

European directive WEEE	not concerned
-------------------------	---------------

**Safety**

---

IK protection code against mechanical impacts	IK10
Protection class	isol.class I
REACH conform	No
RoHS conform	Yes
Fire resistance	-