



FL165A

**Steel enclosure, Orion.Plus, glazed door 600x400x250 mm**

**Technical properties**

**Architecture**

Fixing mode Wall mounting

**Functions**

Cover with overpressure release No

**Compatibility**

Suitable for lightning protection No

**Electric current**

Rated current 630 A

**Dimensions**

Insertion depth 250 mm

Depth of installed product 250 mm

Internal depth 250 mm

Height of installed product 600 mm

Width of installed product 400 mm

Thickness of sidewall material 2 mm

**Cover, door**

Material thickness cover 1.5 mm

Type of door closing lock with male triangular wrench

Interlockable Yes

Cover type With Notch

Door leave single

Cover type Door

Transparent cover or door Yes

**Materials**

Colour RAL 7035

Colour light grey

RAL colour RAL 7035 - Light grey

Material Steel

Type of surface treatment powder-coated

**Installation, mounting**

Suitable for outdoor use No

**Equipment**

Number of keys 2

|   |               |
|---|---------------|
| Number of openings for flange plates          | 2             |
| Extension possible                            | No            |
| <b>Standards</b>                              |               |
| European directive WEEE                       | not concerned |
| <b>Safety</b>                                 |               |
| IK protection code against mechanical impacts | IK10          |
| Protection class                              | isol.class I  |
| REACH conform                                 | No            |
| RoHS conform                                  | Yes           |
| Fire resistance                               | -             |