

No



Steel enclosure, Orion.Plus, glazed door 800x500x200 mm

Technical propertie	5
---------------------	---

Fixing mode Functions Cover with overpressure release No Configuration Number of modules 110 Compatibility Suitable for lightning protection No Electric current Rated current 630 A Dimensions Insertion depth 200 mm Internal depth 200 mm Height of installed product 101 101 101 101 101 101 101 1	Architecture	
Cover with overpressure release No Configuration Number of modules 110 Compatibility Suitable for lightning protection No Electric current Rated current 630 A Dimensions Insertion depth 200 mm Depth of installed product 200 mm Internal depth 200 mm Height of installed product 800 mm Width of installed product 500 mm Thickness of sidewall material 1.2 mm Cover, door Material thickness cover 1.5 mm Type of door closing lock with male triangular wrench Interlockable Yes Cover type Closed (plain) Door leave single Cover type Door Transparent cover or door Yes Materials Colour RAL 7035 Colour RAL 7035	Fixing mode	Wall mounting
Configuration Number of modules 110 Compatibility Suitable for lightning protection No Electric current 800 mm Rated current 630 A Dimensions 200 mm Insertion depth 200 mm Depth of installed product 200 mm Internal depth 200 mm Height of installed product 800 mm Width of installed product 500 mm Thickness of sidewall material 1.2 mm Cover, door 1.5 mm Type of door closing lock with male triangular wrench Interlockable Yes Cover type Closed (plain) Door leave single Cover type Door Transparent cover or door Yes Materials Steel Colour RAL 7035 - Light grey RAL colour RAL 7035 - Light grey Material Steel Type of surface treatment powder-coated	Functions	
Number of modules 110 Compatibility Suitable for lightning protection No Electric current Rated current 630 A Dimensions Insertion depth 200 mm Depth of installed product 200 mm Internal depth 200 mm Width of installed product 800 mm Width of installed product 500 mm Thickness of sidewall material 1.2 mm Cover, door Material thickness cover 1.5 mm Type of door closing lock with male triangular wrench interlockable Yes Cover type Closed (plain) Door leave single Cover type Door Transparent cover or door Yes Materials Colour RAL 7035 Colour light grey RAL colour RAL 7035 Coleur RAL 7035 - Light grey Material Steel Type of surface treatment powder-coated	Cover with overpressure release	No
Compatibility Suitable for lightning protection No Electric current Rated current 630 A Dimensions Insertion depth 200 mm Depth of installed product 200 mm Internal depth 200 mm Height of installed product 800 mm Width of installed product 500 mm Width of installed product 500 mm Thickness of sidewall material 1.2 mm Cover, door Material thickness cover 1.5 mm Type of door closing lock with male triangular wrench Interlockable Yes Cover type Closed (plain) Door leave single Cover type Door Transparent cover or door Yes Materials Colour RAL 7035 Colour light grey RAL colour RAL 7035 Colour RAL 7035 - Light grey Material Steel Type of surface treatment powder-coated	Configuration	
Suitable for lightning protection Flectric current Rated current 630 A Dimensions Insertion depth 200 mm Depth of installed product 200 mm Internal depth 200 mm Height of installed product 800 mm Width of installed product 500 mm Thickness of sidewall material 1,2 mm Cover, door Material thickness cover 1,5 mm Type of door closing lock with male triangular wrench Interlockable Yes Cover type Closed (plain) Door leave single Cover type Door Transparent cover or door Yes Materials Colour RAL 7035 Coleur RAL colour RAL 7035 Coteel Type of surface treatment powder-coated	Number of modules	110
Suitable for lightning protection Flectric current Rated current 630 A Dimensions Insertion depth 200 mm Depth of installed product 200 mm Internal depth 200 mm Height of installed product 800 mm Width of installed product 500 mm Thickness of sidewall material 1,2 mm Cover, door Material thickness cover 1,5 mm Type of door closing lock with male triangular wrench Interlockable Yes Cover type Closed (plain) Door leave single Cover type Door Transparent cover or door Yes Materials Colour RAL 7035 Coleur RAL colour RAL 7035 Coteel Type of surface treatment powder-coated	Compatibility	
Rated current 630 A Dimensions Insertion depth 200 mm Depth of installed product 200 mm Internal depth 200 mm Height of installed product 800 mm Width of installed product 500 mm Thickness of sidewall material 1.2 mm Cover, door Material thickness cover 1.5 mm Type of door closing lock with male triangular wrench interlockable Yes Cover type Closed (plain) Door leave single Cover type Door Transparent cover or door Yes Materials Colour RAL 7035 Colour RAL 7035 - Light grey Material Steel Type of surface treatment powder-coated		No
Rated current 630 A Dimensions Insertion depth 200 mm Depth of installed product 200 mm Internal depth 200 mm Height of installed product 800 mm Width of installed product 500 mm Thickness of sidewall material 1.2 mm Cover, door Material thickness cover 1.5 mm Type of door closing lock with male triangular wrench interlockable Yes Cover type Closed (plain) Door leave single Cover type Door Transparent cover or door Yes Materials Colour RAL 7035 Colour RAL 7035 - Light grey Material Steel Type of surface treatment powder-coated	-1	
Dimensions Insertion depth 200 mm Depth of installed product 200 mm Internal depth 200 mm Height of installed product 800 mm Width of installed product 500 mm Thickness of sidewall material 1.2 mm Cover, door Material thickness cover 1.5 mm Type of door closing lock with male triangular wrench Interlockable Yes Cover type Closed (plain) Door leave single Cover type Door Transparent cover or door Yes Materials Colour RAL 7035 Colour RAL 7035 - Light grey Material Steel Type of surface treatment powder-coated		
Insertion depth 200 mm Depth of installed product 200 mm Internal depth 200 mm Height of installed product 800 mm Width of installed product 500 mm Width of installed product 500 mm Thickness of sidewall material 1.2 mm Cover, door Material thickness cover 1.5 mm Type of door closing lock with male triangular wrench Interlockable Yes Cover type Closed (plain) Door leave single Cover type Door Transparent cover or door Yes Materials Colour RAL 7035 Colour RAL 7035 - Light grey Material Steel Type of surface treatment powder-coated	Rated current	630 A
Depth of installed product 200 mm Internal depth 200 mm Height of installed product 800 mm Width of installed product 500 mm Thickness of sidewall material 1.2 mm Cover, door Material thickness cover 1.5 mm Type of door closing lock with male triangular wrench Interlockable Yes Cover type Closed (plain) Door leave single Cover type Door Transparent cover or door Yes Materials Colour RAL 7035 Colour light grey RAL colour RAL 7035 - Light grey Material Steel Type of surface treatment powder-coated	Dimensions	
Internal depth 200 mm Height of installed product 800 mm Width of installed product 500 mm Thickness of sidewall material 1.2 mm Cover, door Material thickness cover 1.5 mm Type of door closing lock with male triangular wrench Interlockable Yes Cover type Closed (plain) Door leave single Cover type Door Transparent cover or door Yes Materials Colour RAL 7035 Colour RAL 7035 - Light grey Material Steel Type of surface treatment powder-coated	Insertion depth	200 mm
Height of installed product 500 mm Width of installed product 500 mm Thickness of sidewall material 1.2 mm Cover, door Material thickness cover 1.5 mm Type of door closing lock with male triangular wrench Interlockable Yes Cover type Closed (plain) Door leave single Cover type Door Transparent cover or door Yes Materials Colour RAL 7035 Colour RAL 7035 - Light grey Material Steel Type of surface treatment powder-coated	Depth of installed product	200 mm
Width of installed product 500 mm Thickness of sidewall material 1.2 mm Cover, door Material thickness cover 1.5 mm Type of door closing lock with male triangular wrench Interlockable Yes Cover type Closed (plain) Door leave single Cover type Door Transparent cover or door Yes Materials Colour RAL 7035 Colour RAL 7035 - Light grey RAL colour RAL 7035 - Light grey Material Steel Type of surface treatment powder-coated	Internal depth	200 mm
Thickness of sidewall material 1.2 mm Cover, door Material thickness cover 1.5 mm Type of door closing lock with male triangular wrench Interlockable Yes Cover type Closed (plain) Door leave single Cover type Door Transparent cover or door Yes Materials Colour RAL 7035 Colour RAL 7035 - Light grey Material Steel Type of surface treatment powder-coated	Height of installed product	800 mm
Cover, door Material thickness cover 1.5 mm Type of door closing lock with male triangular wrench Interlockable Yes Cover type Closed (plain) Door leave single Cover type Door Transparent cover or door Yes Materials Colour RAL 7035 Colour light grey RAL colour RAL 7035 - Light grey Material Steel Type of surface treatment powder-coated	Width of installed product	500 mm
Material thickness cover 1.5 mm Type of door closing lock with male triangular wrench Interlockable Yes Cover type Closed (plain) Door leave single Cover type Door Transparent cover or door Yes Materials Colour RAL 7035 Colour light grey RAL colour RAL 7035 - Light grey Material Steel Type of surface treatment powder-coated	Thickness of sidewall material	1.2 mm
Type of door closing lock with male triangular wrench Interlockable Yes Cover type Closed (plain) Door leave single Cover type Door Transparent cover or door Yes Materials Colour RAL 7035 Colour RAL 7035 - Light grey RAL colour Steel Type of surface treatment powder-coated	Cover, door	
Interlockable Yes Cover type Closed (plain) Door leave single Cover type Door Transparent cover or door Yes Materials Colour RAL 7035 Colour light grey RAL colour RAL 7035 - Light grey Material Steel Type of surface treatment powder-coated	Material thickness cover	1.5 mm
Cover type Closed (plain) Door leave Single Cover type Door Transparent cover or door Yes Materials Colour RAL 7035 Colour light grey RAL colour RAL 7035 - Light grey Material Steel Type of surface treatment powder-coated	Type of door closing	lock with male triangular wrench
Door leave Single Cover type Door Transparent cover or door Yes Materials Colour RAL 7035 Colour light grey RAL colour RAL 7035 - Light grey Material Steel Type of surface treatment powder-coated	Interlockable	Yes
Cover type Door Transparent cover or door Yes Materials Colour RAL 7035 Colour light grey RAL colour RAL 7035 - Light grey Material Steel Type of surface treatment powder-coated	Cover type	Closed (plain)
Transparent cover or door Yes Materials Colour RAL 7035 Colour light grey RAL colour RAL 7035 - Light grey Material Steel Type of surface treatment powder-coated	Door leave	single
Materials Colour RAL 7035 Colour light grey RAL colour RAL 7035 - Light grey Material Steel Type of surface treatment powder-coated	Cover type	Door
Colour RAL 7035 Colour light grey RAL colour RAL 7035 - Light grey Material Steel Type of surface treatment powder-coated	Transparent cover or door	Yes
Colour light grey RAL colour RAL 7035 - Light grey Material Steel Type of surface treatment powder-coated	Materials	
RAL colour RAL 7035 - Light grey Material Steel Type of surface treatment powder-coated	Colour	RAL 7035
Material Steel Type of surface treatment powder-coated	Colour	light grey
Type of surface treatment powder-coated	RAL colour	RAL 7035 - Light grey
	Material	Steel
Installation, mounting	Type of surface treatment	powder-coated
	Installation, mounting	

Suitable for outdoor use

Equipment	
Number of rows	5
Number of keys	2
Number of openings for flange plates	2
Extension possible	Yes
Standards	
European directive WEEE	not concerned
Safety	
IK protection code against mecanical	
impacts	IK10
Protection class	isol.class I
REACH conform	No
RoHS conform	Yes
Fire resistance	-