Product data sheet FL173A





FL173A

Steel enclosure, Orion.Plus, glazed door 800x600x250 mm

Technical properties

Fixing mode	Wall mounting
Functions	
Cover with overpressure release	No
Configuration	
Number of modules	130
Compatibility	
Suitable for lightning protection	Nc
Electric current	
Rated current	630 A
Dimensions	
Insertion depth	250 mm
Denth of installed avadust	
Depth of installed product	250 mm
Depth of installed product Internal depth	
Internal depth	250 mm
Internal depth Height of installed product	250 mm 800 mm
	250 mm 800 mm 600 mm
Internal depth Height of installed product Width of installed product Thickness of sidewall material	250 mm 800 mm 600 mm
Internal depth Height of installed product Width of installed product Thickness of sidewall material Cover, door	250 mm 800 mm 600 mm 1.2 mm
Internal depth Height of installed product Width of installed product Thickness of sidewall material Cover, door Material thickness cover	250 mm 800 mm 600 mm 1.2 mm 1.5 mm
Internal depth Height of installed product Width of installed product	250 mm 250 mm 800 mm 600 mm 1.2 mm 1.5 mm lock with male triangular wrench Yes

Number of Reylock of the door	Σ.
Cover type	Closed (plain)
Door leave	single
Cover type	Door
Transparent cover or door	Yes

Materials

Colour	RAL 7035
Colour	light grey
RAL colour	RAL 7035 - Light grey
Material	Steel
Type of surface treatment	powder-coated

Installation, mounting

Suitable for outdoor use	No
Equipment	
Number of rows	
Number of keys	
Number of openings for flange plates	
Extension possible	Ye
Standards	
European directive WEEE	not concerne
Safety	
IK protection code against mecanical impacts	IK1
Protection class	isol.class
REACH conform	Ν