



LS770

**Microswitch 1P for fuse carrier L58**

**Technical properties**

**Architecture**

Number of poles	1 P
-----------------	-----

**Main electrical features**

Rated operational voltage Ue	220 / 250 V
------------------------------	-------------

**Voltage**

Rated insulation voltage	6000 V
--------------------------	--------

Rated operational voltage in DC	24 / 220 V
---------------------------------	------------

**Electric current**

Acceptable current rating with AC1	5 A
------------------------------------	-----

I <sub>min</sub> = f (U = 230 V AC)	5 A
-------------------------------------	-----

**Dimensions**

Depth of installed product	20 mm
----------------------------	-------

Height of installed product	35 mm
-----------------------------	-------

Width of installed product	35 mm
----------------------------	-------

**Equipment**

Quantity of NC contacts	0
-------------------------	---

Quantity of NO contacts	0
-------------------------	---

Quantity of INV contacts	1
--------------------------	---

**Standards**

European directive WEEE	concerned
-------------------------	-----------

**Safety**

REACH conform	Yes
---------------	-----

RoHS conform	Yes
--------------	-----

Halogen free	Yes
--------------	-----

**Use conditions**

Operating temperature	-5...40 °C
-----------------------	------------

Storage/transport temperature	-25...55 °C
-------------------------------	-------------