



UC971

Earth cross rail, quadro.system, 12x5 L250 mm

Technical properties

Electric current

| | |
|---------------|-------|
| Rated current | 160 A |
|---------------|-------|

Dimensions

| | |
|----------------------------|------|
| Depth of installed product | 5 mm |
|----------------------------|------|

| | |
|-----------------------------|-------|
| Height of installed product | 12 mm |
|-----------------------------|-------|

| | |
|--------|--------|
| Length | 250 mm |
|--------|--------|

| | |
|----------------------------|--------|
| Width of installed product | 245 mm |
|----------------------------|--------|

| | |
|---------------------------|------|
| Height of the busbar bars | 5 mm |
|---------------------------|------|

| | |
|----------------------|-------|
| Width of the busbars | 12 mm |
|----------------------|-------|

Materials

| | |
|----------|--------|
| Material | Copper |
|----------|--------|

Equipment

| | |
|------------------------------|---|
| Quantity of section in width | 1 |
|------------------------------|---|

Standards

| | |
|-------------------------|---------------|
| European directive WEEE | not concerned |
|-------------------------|---------------|

Safety

| | |
|---------------|----|
| REACH conform | No |
|---------------|----|

| | |
|--------------|-----|
| RoHS conform | Yes |
|--------------|-----|