



FL259B

**Polyester enclosure, Orion.Plus, glazed door 500x300x200 mm**

**Technical properties**

**Architecture**

Fixing mode Wall mounting

**Functions**

Cover with overpressure release No

**Configuration**

Number of modules 36

**Compatibility**

Suitable for lightning protection No

**Electric current**

Rated current 630 A

**Dimensions**

Depth of installed product 200 mm

Internal depth 200 mm

Height of installed product 500 mm

Width of installed product 300 mm

Thickness of sidewall material 3 mm

**Cover, door**

Type of door closing lock with male triangular wrench

Interlockable Yes

Number of keylock of the door 2

Cover type Closed (plain)

Door leave single

Cover type Door

Transparent cover or door Yes

**Materials**

Colour RAL 7035

Colour light grey

RAL colour RAL 7035 - Light grey

Material glas reinforced polyester

Type of surface treatment untreated

**Installation, mounting**

Suitable for outdoor use Yes

**Equipment**

Number of rows	3
Number of keys	2
Quantity of rails	3
Number of openings for flange plates	0

**Standards**

Approvals	BS EN 62208
European directive WEEE	not concerned

**Safety**

Protection index IP	IP66
Protection class	isol.class II
REACH conform	No
RoHS conform	Yes