

Yes



## Polyester enclosure, Orion.Plus, plain door 650x500x250 mm

## **Technical properties**

| Architecture                      |                                  |
|-----------------------------------|----------------------------------|
| Fixing mode                       | Wall mounting                    |
| Functions                         |                                  |
| Cover with overpressure release   | No                               |
| Configuration                     |                                  |
| Number of modules                 | 96                               |
|                                   |                                  |
| Compatibility                     |                                  |
| Suitable for lightning protection | No                               |
| Electric current                  |                                  |
| Rated current                     | 630 A                            |
| Dimensions                        |                                  |
| Depth of installed product        | 250 mm                           |
| Internal depth                    | 250 mm                           |
| Height of installed product       | 650 mm                           |
| Width of installed product        | 500 mm                           |
| Width in division units           | 24                               |
| Thickness of sidewall material    | 2 mm                             |
| Cover, door                       |                                  |
| Type of door closing              | lock with male triangular wrench |
| Interlockable                     | Yes                              |
| Number of keylock of the door     | 2                                |
| Cover type                        | Closed (plain)                   |
| Door leave                        | single                           |
| Cover type                        | Door                             |
| Transparent cover or door         | No                               |
| Materials                         |                                  |
| Colour                            | RAL 7035                         |
| Colour                            | light grey                       |
| RAL colour                        | RAL 7035 - Light grey            |
| Material                          | glas reeinforced polyester       |
| Type of surface treatment         | untreated                        |
| Installation, mounting            |                                  |

Suitable for outdoor use

| Equipment                                    |               |
|--|---------------|
| Number of rows                               | 4             |
| Number of keys                               | 2             |
| Quantity of rails                            | 4             |
| Number of openings for flange plates         | 0             |
| Standards                                    |               |
| Approvals                                    | BS EN 62208   |
| European directive WEEE                      | concerned     |
| Safety                                       |               |
| IK protection code against mecanical impacts | IK10          |
| Protection index IP                          | IP66          |
| Protection class                             | isol.class II |
| REACH conform                                | No            |
| RoHS conform                                 | Yes           |