



VS122TJ

**Small distributor,golf,surface,1row,IP40,22M,MS-terminal,N+PE,transparent door**

### Technical properties

#### Architecture

Fixing mode surface-mounting

#### Functions

With a pipe-in lead Yes

#### Configuration

Number of modules 22

#### Main electrical features

Nominal voltage 400 V

#### Electric current

Rated current 63 A

#### Dimensions

Depth of installed product 99 mm

Internal depth 99 mm

Height of installed product 252 mm

Width of installed product 462 mm

#### Cover, door

Identification of protection index 40

Interlockable No

Number of keylock of the door 0

Cover type Closed (plain)

Door locking without

Door leave single

Cover type Door

Transparent cover or door Yes

#### Materials

Colour pure white

Colour white

RAL colour RAL 9010 - Pure white

Material plastic

Type of surface treatment untreated

#### Installation, mounting

Suitable for outdoor use No

**Settings**

---

Enclosure type	Distributor empty cabinet
----------------	---------------------------

**Equipment**

---

Number of rows	1
Quantity of section in width	1
Quantity of rails	1
Can be accessorized	Yes
Number of openings for flange plates	0
Extension possible	Yes
Earthing terminal block	Yes
Neutral terminal block	Yes
Signal passing door	Yes

**Standards**

---

GWT Glow wire test	650 °C
European directive WEEE	concerned

**Safety**

---

IK protection code against mechanical impacts	IK07
Protection index IP	IP40
Protection class	isol.class II
REACH conform	No
RoHS conform	Yes

**Use conditions**

---

Operating temperature	-25...40 °C
-----------------------	-------------