

white

RAL 9010 - Pure white



## VF108TJ



## Small distributor,golf,flush,1row,8M,IP40,MS-terminal,N+PE,transparent door

## **Technical properties**

| Architecture                       |                |
|------------------------------------|----------------|
| Fixing mode                        | flush-mounting |
| Functions                          |                |
| With a pipe-in lead                | Yes            |
| Configuration                      |                |
| Number of modules                  | 8              |
|                                    |                |
| Main electrical features           |                |
| Nominal voltage                    | 400 V          |
| Electric current                   |                |
| Rated current                      | 63 A           |
| Dimensions                         |                |
| Insertion depth                    | 72 mm          |
| Depth of wall niche                | 72 mm          |
| Depth of installed product         | 97.5 mm        |
| Internal depth                     | 97.5 mm        |
| Height of installed product        | 225 mm         |
| Installation height                | 189 mm         |
| Width of installed product         | 275 mm         |
| Built-in height                    | 189 mm         |
| Built-in width                     | 242 mm         |
| Cover, door                        |                |
| Identification od protection index | 40             |
| Interlockable                      | No             |
| Number of keylock of the door      | 0              |
| Cover type                         | Closed (plain) |
| Door locking                       | without        |
| Door leave                         | single         |
| Cover type                         | Door           |
| Transparent cover or door          | Yes            |
| Materials                          |                |
| Colour                             | pure white     |
|                                    |                |

Colour

RAL colour

| Material                                     | plastic                   |
|--|---------------------------|
| Type of surface treatment                    | untreated                 |
| Installation, mounting                       |                           |
| Suitable for outdoor use                     | No                        |
|  |                           |
| Settings                                     |                           |
| Enclosure type                               | Distributor empty cabinet |
| Equipment                                    |                           |
| Number of rows                               | 1                         |
| Quantity of section in width                 | 1                         |
| Quantity of rails                            | 1                         |
| Can be accessorized                          | Yes                       |
| Number of openings for flange plates         | 0                         |
| Extension possible                           | Yes                       |
| Earthing terminal block                      | Yes                       |
| Neutral terminal block                       | Yes                       |
| Signal passing door                          | Yes                       |
| Standards                                    |                           |
| GWT Glow wire test                           | 650 °C                    |
| European directive WEEE                      | concerned                 |
| Safety                                       |                           |
| IK protection code against mecanical impacts | 07                        |
| Protection class                             | isol.class II             |
| REACH conform                                | Yes                       |
| RoHS conform                                 | Yes                       |
| Use conditions                               |                           |
| Operating temperature                        | -2540 °C                  |