



VF218TJ

**Small distributor,golf,flush,2row,36M,IP40,MS-terminal,N+PE,transparent door**

**Technical properties**

**Architecture**

Fixing mode flush-mounting

**Functions**

With a pipe-in lead Yes

**Configuration**

Number of modules 36

**Main electrical features**

Nominal voltage 400 V

**Electric current**

Rated current 63 A

**Dimensions**

Insertion depth 72 mm

Depth of wall niche 72 mm

Depth of installed product 97.5 mm

Internal depth 97.5 mm

Height of installed product 418 mm

Installation height 382 mm

Width of installed product 460 mm

Built-in height 382 mm

Built-in width 426 mm

**Cover, door**

Identification of protection index 40

Interlockable No

Number of keylock of the door 0

Cover type Closed (plain)

Door locking without

Door leave single

Cover type Door

Transparent cover or door Yes

**Materials**

Colour pure white

Colour white

RAL colour RAL 9010 - Pure white

Material	plastic
Type of surface treatment	untreated
<b>Installation, mounting</b>	
Suitable for outdoor use	No
<b>Settings</b>	
Enclosure type	Distributor empty cabinet
<b>Equipment</b>	
Number of rows	2
Quantity of section in width	1
Quantity of rails	2
Can be accessorized	Yes
Number of openings for flange plates	0
Extension possible	Yes
Earthing terminal block	Yes
Neutral terminal block	Yes
Signal passing door	Yes
<b>Standards</b>	
GWT Glow wire test	650 °C
European directive WEEE	concerned
<b>Safety</b>	
IK protection code against mechanical impacts	07
Protection index IP	IP40
Protection class	isol.class II
REACH conform	No
RoHS conform	Yes
Halogen free	Yes
<b>Use conditions</b>	
Operating temperature	-25...40 °C