Product data sheet **FWB52S**





FWB52S

FWB encl., univers, 5-rows 120 modules cl.II IP44 w.plain door, 800x550x161mm, QC

Technical properties

Fixing mode	surface-mounting
Functions	
With a pipe-in lead	Yes
Protection main switch	No
Configuration	
Number of modules	120
Compatibility	
Suitable for Multimedia	No
Electric current	
Rated current	125 A
Dimensions	
Insertion depth	161 mm
Depth of installed product	165 mm
Internal depth	156 mm
Height of installed product	800 mm
Installation height	800 mm
Width of installed product	550 mm
Width in division units	24
Thickness of sidewall material	1 mm
Cover, door	
Number of keylock of the door	1
Door locking	without
Door leave	single
Cover type	Door
Transparent cover or door	No
Materials	
Copper weight of the product	0.081 kg
Colour	white
RAL colour	RAL 9010 - Pure white

Installation, mounting

Suitable for outdoor use

Connection

Number of conduit inlets

Equipment

Number of rows	5
Quantity of section in width	2
Number of keys	1
Quantity of rails	10
Can be accessorized	Yes
Number of openings for flange plates	4
Extension possible	Yes
Earthing terminal block	Yes
Neutral terminal block	Yes
Signal passing door	No

Standards

GWT Glow wire test	750 °C
European directive WEEE	concerned
Protection class according to IEC-61140	

Safety

Protection index IP	IP44
Protection class	isol.class II
REACH conform	No
RoHS conform	Yes
Halogen free	No