

No



FWB43S

FWB enclunivers.4-rows	144	modules of II	IP44 v	v nlain door	650y800y161mm OC
I VVD CIICIuIIIVCI 3.4-10W3		illoudies ci.il	++ V	v.piaiii uooi	OJOVOOOVTOTIIIIII'QC

Technical properties

Architecture	
Fixing mode	surface-mounting
Functions	
With a pipe-in lead	Yes
Protection main switch	No
Configuration	
Number of modules	144
Compatibility	
Suitable for Multimedia	No
Electric current	
Rated current	125 A
Dimensions	
Depth of installed product	165 mm
Internal depth	156 mm
Height of installed product	650 mm
Installation height	650 mm
Width of installed product	800 mm
Thickness of sidewall material	1 mm
Cover, door	
Number of keylock of the door	1
Cover type	With Notch
Door locking	without
Door leave	single
Cover type	Door
Transparent cover or door	No
Materials	
Copper weight of the product	0.123 kg
Colour	white
RAL colour	RAL 9010 - Pure white
Material	sheet steel
Installation, mounting	

Suitable for outdoor use

Connection	
Number of conduit inlets	12
Equipment	
Number of rows	4
Quantity of section in width	3
Number of keys	1
Quantity of rails	12
Can be accessorized	Yes
Number of openings for flange plates	6
Extension possible	Yes
Earthing terminal block	Yes
Neutral terminal block	Yes
Signal passing door	No
Standards	
GWT Glow wire test	750 °C
European directive WEEE	concerned
Protection class according to IEC-61140	II
Safety	
Protection index IP	IP44
Protection class	isol.class II
REACH conform	No
RoHS conform	Yes
Halogen free	No