



FWB44S

**FWB encl.,univers,4-rows 192 modules cl.II IP44 w.plain door, 650x1050x161mm,QC**

**Technical properties**

**Architecture**

Fixing mode surface-mounting

**Functions**

With a pipe-in lead Yes

Protection main switch No

**Configuration**

Number of modules 192

**Compatibility**

Suitable for Multimedia No

**Electric current**

Rated current 125 A

**Dimensions**

Insertion depth 161 mm

Depth of installed product 165 mm

Internal depth 156 mm

Height of installed product 650 mm

Installation height 650 mm

Width of installed product 1050 mm

Thickness of sidewall material 1 mm

**Cover, door**

Number of keylock of the door 1

Cover type With Notch

Door locking without

Door leave single

Cover type Door

Transparent cover or door No

**Materials**

Copper weight of the product 0.162 kg

Colour white

RAL colour RAL 9010 - Pure white

Material sheet steel

**Installation, mounting**

Suitable for outdoor use No

Subject to technical modifications

**Connection**

---

Number of conduit inlets	16
--------------------------	----

---

**Equipment**

---

Number of rows	4
Quantity of section in width	4
Number of keys	1
Quantity of rails	16
Can be accessorized	Yes
Number of openings for flange plates	8
Extension possible	Yes
Earthing terminal block	Yes
Neutral terminal block	Yes
Signal passing door	No

---

**Standards**

---

GWT Glow wire test	750 °C
European directive WEEE	concerned
Protection class according to IEC-61140	II

---

**Safety**

---

Protection index IP	IP44
Protection class	isol.class II
REACH conform	No
RoHS conform	Yes
Halogen free	No

---