



FWB64S

FWB encl.,univers,6-rows 288 modules cl.II IP44 w.plain door, 950x1050x161mm,QC

Technical properties

Architecture

Fixing mode surface-mounting

Functions

With a pipe-in lead Yes

Protection main switch No

Configuration

Number of modules 288

Compatibility

Suitable for Multimedia No

Electric current

Rated current 125 A

Dimensions

Insertion depth 161 mm

Depth of installed product 165 mm

Internal depth 156 mm

Height of installed product 950 mm

Installation height 950 mm

Width of installed product 1050 mm

Thickness of sidewall material 1 mm

Cover, door

Number of keylock of the door 1

Cover type With Notch

Door locking without

Door leave single

Cover type Door

Transparent cover or door No

Materials

Copper weight of the product 0.162 kg

Colour white

RAL colour RAL 9010 - Pure white

Material sheet steel

Installation, mounting

Suitable for outdoor use No

Subject to technical modifications

Connection

| | |
|--------------------------|----|
| Number of conduit inlets | 16 |
|--------------------------|----|

Equipment

| | |
|--------------------------------------|-----|
| Number of rows | 6 |
| Quantity of section in width | 4 |
| Number of keys | 1 |
| Quantity of rails | 24 |
| Can be accessorized | Yes |
| Number of openings for flange plates | 8 |
| Extension possible | Yes |
| Earthing terminal block | Yes |
| Neutral terminal block | Yes |
| Signal passing door | No |

Standards

| | |
|---|-----------|
| GWT Glow wire test | 750 °C |
| European directive WEEE | concerned |
| Protection class according to IEC-61140 | II |

Safety

| | |
|---------------------|---------------|
| Protection index IP | IP44 |
| Protection class | isol.class II |
| REACH conform | No |
| RoHS conform | Yes |
| Halogen free | No |
