



FM207

**Floor standing steel enclosure, Quadro5, 1710x700x260 mm**

**Technical properties**

**Functions**

|                                 |    |
|---------------------------------|----|
| Cover with overpressure release | No |
|---------------------------------|----|

**Configuration**

|                   |     |
|-------------------|-----|
| Number of modules | 240 |
|-------------------|-----|

**Compatibility**

|                                   |    |
|-----------------------------------|----|
| Suitable for lightning protection | No |
|-----------------------------------|----|

**Electric current**

|               |       |
|---------------|-------|
| Rated current | 630 A |
|---------------|-------|

**Dimensions**

|                                |         |
|--------------------------------|---------|
| Insertion depth                | 260 mm  |
| Depth of installed product     | 260 mm  |
| Internal depth                 | 260 mm  |
| Height of installed product    | 1710 mm |
| Width of installed product     | 700 mm  |
| Width in division units        | 24      |
| Thickness of sidewall material | 2 mm    |

**Cover, door**

|                           |                |
|---------------------------|----------------|
| Material thickness cover  | 2 mm           |
| Cover type                | Closed (plain) |
| Door leave                | single         |
| Cover type                | Door           |
| Transparent cover or door | No             |

**Materials**

|                           |                       |
|---------------------------|-----------------------|
| Colour                    | pure white            |
| Colour                    | white                 |
| RAL colour                | RAL 9010 - Pure white |
| Material                  | Steel                 |
| Type of surface treatment | powder-coated         |

**Installation, mounting**

|                          |    |
|--------------------------|----|
| Suitable for outdoor use | No |
|--------------------------|----|

**Equipment**

|                              |    |
|------------------------------|----|
| Number of rows               | 10 |
| Quantity of section in width | 2  |

Subject to technical modifications

|                                               |           |
|-----------------------------------------------|-----------|
| Number of openings for flange plates          | 2         |
| Extension possible                            | Yes       |
| <b>Standards</b>                              |           |
| European directive WEEE                       | concerned |
| <b>Safety</b>                                 |           |
| IK protection code against mechanical impacts | IK10      |
| Protection index IP                           | IP55      |
| REACH conform                                 | No        |
| Fire resistance                               | -         |