



VE106L

**Enclosure,vector,IP5x,6Modules,version Austria**

**Technical properties**

**Architecture**

Fixing mode surface-mounting

**Functions**

With a pipe-in lead Yes

**Configuration**

Number of modules 6

**Main electrical features**

Nominal voltage 400 V

**Electric current**

Rated current 63 A

**Dimensions**

Depth of installed product 113 mm

Internal depth 113 mm

Height of installed product 190 mm

Width of installed product 165 mm

Thickness of sidewall material 2.5 mm

**Cover, door**

Identification of protection index 65

Interlockable No

Number of keylock of the door 0

Cover type Closed (plain)

Door locking without

Door leave single

Cover type Door

Transparent cover or door Yes

**Materials**

Colour light grey

Colour light grey

RAL colour RAL 7035 - Light grey

Material Polystyrol (PS)

Type of surface treatment untreated

**Installation, mounting**

Suitable for outdoor use No

Subject to technical modifications

---

**Connection**

Number of conduit inlets	3
--------------------------	---

---

**Settings**

Enclosure type	Distributor empty cabinet
----------------	---------------------------

---

**Equipment**

Number of rows	1
----------------	---

Quantity of section in width	1
------------------------------	---

Quantity of rails	1
-------------------	---

Can be accessorized	Yes
---------------------	-----

Number of openings for flange plates	16
--------------------------------------	----

Extension possible	No
--------------------	----

Earthing terminal block	No
-------------------------	----

Neutral terminal block	No
------------------------	----

Signal passing door	Yes
---------------------	-----

---

**Standards**

GWT Glow wire test	750 °C
--------------------	--------

European directive WEEE	concerned
-------------------------	-----------

---

**Safety**

IK protection code against mechanical impacts	IK07
---	------

Protection class	isol.class II
------------------	---------------

REACH conform	No
---------------	----

---

**Use conditions**

Operating temperature	-25...40 °C
-----------------------	-------------