



VE218L

**Enclosure, vector, IP5x, 36Modules,version Austria**

**Technical properties**

**Architecture**

Fixing mode surface-mounting

**Functions**

With a pipe-in lead Yes

**Configuration**

Number of modules 36

**Main electrical features**

Nominal voltage 400 V

**Electric current**

Rated current 63 A

**Dimensions**

Depth of installed product 151 mm

Internal depth 151 mm

Height of installed product 452 mm

Width of installed product 418 mm

Thickness of sidewall material 2.5 mm

**Cover, door**

Identification od protection index 65

Interlockable No

Number of keylock of the door 0

Cover type Closed (plain)

Door locking without

Door leave single

Cover type Door

Transparent cover or door Yes

**Materials**

Colour light grey

Colour light grey

RAL colour RAL 7035 - Light grey

Material Polystyrol (PS)

Type of surface treatment untreated

**Installation, mounting**

Suitable for outdoor use No

Subject to technical modifications

**Connection**

---

Number of conduit inlets	15
--------------------------	----

**Settings**

---

Enclosure type	Distributor empty cabinet
----------------	---------------------------

**Equipment**

---

Number of rows	2
Quantity of section in width	1
Quantity of rails	2
Can be accessorized	Yes
Number of openings for flange plates	46
Extension possible	No
Earthing terminal block	No
Neutral terminal block	No
Signal passing door	Yes

**Standards**

---

GWT Glow wire test	750 °C
European directive WEEE	concerned

**Safety**

---

IK protection code against mechanical impacts	07
Protection class	isol.class II
REACH conform	No
RoHS conform	Yes

**Use conditions**

---

Operating temperature	-25...40 °C
-----------------------	-------------