



KDN363A

Insulated busbar 3P 63A fork 10mm² 12M

Technical properties

Architecture

| | |
|-----------------|-----|
| Number of poles | 3 P |
| Type of pole | 3 P |

Compatibility

| | |
|--|-----------------|
| Intended for the compatible references | Modular devices |
|--|-----------------|

Main electrical features

| | |
|------------------------------|-------------|
| Rated operational voltage Ue | 230 / 400 V |
|------------------------------|-------------|

Voltage

| | |
|-----------------------|-------|
| Max operating voltage | 400 V |
|-----------------------|-------|

Electric current

| | |
|---------------|------|
| Rated current | 63 A |
|---------------|------|

Dimensions

| | |
|--------|---------|
| Length | 210 mm |
| Pitch | 17.8 mm |

Materials

| | |
|--------|------------|
| Colour | stone grey |
|--------|------------|

Installation, mounting

| | |
|--|----|
| Suitable to a device with an auxiliary | No |
|--|----|

Connection

| | |
|--|-------------------|
| Connection cross-sect. rigid cable | 10mm ² |
| Suitable for product with neutral busbar | No |

Equipment

| | |
|-----------------------|------|
| Number of connections | 12 C |
|-----------------------|------|

Standards

| | |
|-------------------------|-----------|
| European directive WEEE | concerned |
|-------------------------|-----------|

Safety

| | |
|---------------|-----|
| REACH conform | No |
| RoHS conform | Yes |

Use conditions

| | |
|-----------|-----|
| Insulated | Yes |
|-----------|-----|