



EEN101



IP20

## Twilight switch 1 channel, 1M, flush mounted cell

### Technical properties

#### Architecture

Fixing mode	Din-Rail
-------------	----------

#### Configuration

Number of modules	1
-------------------	---

#### Controls and indicators

Presence button	No
-----------------	----

#### Main electrical features

Rated operational voltage $U_e$	230 V
---------------------------------	-------

Frequency	50/60 Hz
-----------	----------

#### Electric current

Max. power with $\cos \phi$ 0.6	10 A
---------------------------------	------

#### Dimensions

Depth of installed product	65 mm
----------------------------	-------

Height of installed product	83 mm
-----------------------------	-------

Width of installed product	17.8 mm
----------------------------	---------

#### Frequency

Frequency range	50...60 Hz
-----------------	------------

#### Power

Fluorescent lamps duo circuit	1000 W
-------------------------------	--------

Max. power with fluo uncompensated lamps	1000 VA
--	---------

Power consumed	0.3 VA
----------------	--------

Power consumption (operation)	300 mW
-------------------------------	--------

Incandescent bulb power	2300 W
-------------------------	--------

Total power loss under IN	0.3 W
---------------------------	-------

Power dissipation per coil	0.3 W
----------------------------	-------

Max. Breaking capacity for parallel compensated fluorescent tubes	200 W
---	-------

Max. Breaking capacity for row-compensated fluorescent tubes	1000 W
--	--------

#### Endurance

Electrical endurance cycles with incandescent lighting	7500
--	------

Electrical durability at nominal load in AC1 in operating cycles	50000
--	-------

Electrical durability with parallel compensated fluorescent tubes	4000
---	------

Electrical durability with row-compensated fluorescent tubes	7500
--	------

### Lighting control

Brightness measurement range	5 / 2000 Lux
------------------------------	--------------

### Fluorescent bulbs control

Max. power with fluorescent parallel lamps	1000 VA
--	---------

Max. power fluo. duo lamp comp. series	1000 W
--	--------

Fluorescent lamps parallel compensated	1000 W
--	--------

Fluorescent lamps uncompensated	1000 W
---------------------------------	--------

### Incandescent bulbs control

Max. power with incandescent lamps	2300 W
------------------------------------	--------

### Installation, mounting

Mounting type	din-Rail
---------------	----------

Installation mode	for mounting on DIN rail
-------------------	--------------------------

### Connection

Number of contacts	1
--------------------	---

Type of connection	with screw terminals
--------------------	----------------------

### Settings

Delay ON	60 s
----------	------

Delay OFF	80 s
-----------	------

### Safety

Protection index IP	IP20
---------------------	------

REACH conform	No
---------------	----

RoHS conform	Yes
--------------	-----

Halogen free	No
--------------	----