





















## **Remote Control Dimmer universal 500W**

# **Technical properties**

Fixing mode Din-Rail

## Configuration

Number of modules 2

#### Main electrical features

Rated operational voltage Ue 230 V
Frequency 50/60 Hz

#### Voltage

DC control voltage 24 / 110 V DC

Command voltage AC 24 / 230 V AC

#### Fuse

Fuse with electronic short-circuit and overload protection

## Dimensions

Depth of installed product 62 mm
Height of installed product 85 mm
Installation height 0 / 1000 m
Width of installed product 35 mm
Width of rail mounted device (RMD) 2 modules

## Length

Max distance to switches 50 mm

## Power

Dimmable conventional transformers	500 VA
Halogen switching capacity 230V	500 W
Power consumed	4.5 W
Power consumption (operation)	4.5 W
Power consumption (standby)	0.2 W
Incandescent bulb power	500 W
Total power loss under IN	0.2 W
Conventional transformers	500 VA
Electronic transformers	500 W

# Materials

RAL colour RAL 9001 - Cream Surface appearance matt

100 W 100 W 100 W 500 W din-Rail
100 W 100 W 100 W 500 W din-Rail
100 W 100 W 500 W 500 W
100 W 500 W 500 W din-Rail
500 W 500 W din-Rail
500 W din-Rail
500 W din-Rail
din-Rail
din-Rail mounting on DIN rail
mounting on DIN rail
1 / 6mm²
1 / 6mm²
universal
1.56 mm²
1.56 mm²
with screw terminals
with screw
max. 50 m
No
IP20
No
-2050 °C
-2050 °C

Only for use with dimmable lamps!

Information text