




EZN005



IP40



Symmetrical Flasher

Technical properties

Architecture

Fixing mode Din-Rail

Functions

Switching cycles min. 50000

Configuration

Switch mode change-over contact, usable as NC or NO

Number of modules 1

Main electrical features

Rated operational voltage U_e 12 / 230 V

Frequency 50/60 Hz

Electric current

Max. power with $\cos \phi$ 0.6 5 A

Switching current at $\cos \phi = 0.6$ max. 5 A

Dimensions

Depth of installed product 58 mm

Height of installed product 85 mm

Length 64 mm

Width of installed product 17.5 mm

Width of rail mounted device (RMD) 1 modules

Power

Power consumed 15 VA

Power consumption (operation) 15 VA

Total power loss under IN 2 W

Loss power at full load \approx 2 W

Power dissipation per coil 0.5 W

Incandescent bulbs control

Max. power with incandescent lamps 450 W

230 V incandescent lamps and halogen lamps max. 450 W

Installation, mounting

Mounting type din-Rail

Installation mode for mounting on DIN rail

Connection

| | |
|---|--------------------------|
| Connection cross-sect. flexible conductor | 1 / 6mm ² |
| Conductor cross-section (flexible) | 1...6 mm ² |
| Conductor cross-section (rigid) | 1.5...10 mm ² |
| Number of contacts | 1 |
| Type of contacts | 1 changeover |
| Type of connection | with screw terminals |
| Type of connection | with screw |

Settings

| | |
|------------------------|--------------|
| Delay ON | 0.1 s |
| Delay time, adjustable | 0.1 s...10 h |
| Delay OFF | 0.1 s |

Safety

| | |
|---------------------|------|
| Protection index IP | IP40 |
| REACH conform | Yes |
| RoHS conform | Yes |

Use conditions

| | |
|-------------------------------|-------------|
| Operating temperature | -20...50 °C |
| Storage/transport temperature | -40...70 °C |

Instructions

| | |
|-------------------|---|
| Special note text | Notice: Not suitable for connection to safety extra-low voltage (SELV). |
|-------------------|---|